

Soft dB is proud to present The 2nd generation Piccolo Sound Level Meter



Professional Integrating and Data Logging Class 2 SLM

- Fully complies with ISO 61672 and ANSI S1.4 (vs ISO 831); **Improved!**
- Frequency span 20Hz to 16kHz (vs 31 to 8kHz); **Improved!**
- Level ranges: Lo: 30 dBA to 110 dBzPk (vs 37 to 105 dBA)
Hi: 40 dBA to 130 dBzPk ; **New!**

Simultaneous measurements

- Leq, Lmax, Lmin, Lpeak, in A, C, and Z weighting; **New!**
- Ln% for a selected weighting, 0.1 dB resolution; **Improved!**
- 31.5Hz to 8kHz octave bands; **New!**
- 400 lines FFT; **New!**

Internal lithium USB rechargeable battery **New!**

- 48 hours autonomy
- Unlimited autonomy using an External USB charger

Impressive storage capacity:

All data, including Leq, Lmax, Lpeak, Lmin, Ln%, oct. band & 400 lines FFT:

- Up to 2 years for 1 hour averaging time, Leq (1h);
- Up to 2 months for 5 min. averaging time, Leq (5min);
- Up to 2 weeks for 1min. averaging time, Leq (1min);

Unparalleled performance for only 495\$USD

No doubt, the most interesting SLM Class 2 on the market !

As the 1st gen:

- Very easy to use;
- Compact and lightweight;
- Ultra low power consumption;

It is ideal for:

- Environmental noise survey;
- long term noise monitoring

CONTACT

Soft dB
Instruments and Softwares

1040 Belvédère av.
Suite 215
Québec (Qc) Canada
G1S3G3

Phone: +1 418-686-0993
Toll Free: 1 888-686-0993
Fax: 418-686-2043

SOFTDB.COM/piccololl/