

Demonstration and calibration kit



smartSMS-NET Sound Masking System

Each **Demo Kit** includes:

- ML12 Controller
- 50W Power Supply
- SMS-STR Sound Masking Structure Speaker
- Active Control Sensor
- One Volume control knob
- Calibration Microphone (2 possible options)
- Transportation Case
- SMS-Router



Specifications

| DEMO KIT | | |
|-------------------------|--|---|
| ML12 Controller | Project Master, 2 Outputs, Max 6 Speakers/Output, Max 12 Speakers/Controller, 2 Active Outputs Soft dB Controllers Specs | |
| Power Supply | 50W Supply | |
| SMS-STR | Certification UL 62368 / UL204, Color White (RAL9016), typically used in open ceiling configuration and in the plenum space. Soft dB Speakers Specs | |
| Active Control Sensor | Adjustable down to 0.1dB steps, updates every 15s SMS-SEN Specs | |
| Volume control knob | Controls sound masking and/or music on any given zone or group of zones. Volume control knob Specs | |
| Transportation Case | As shown on the picture | |
| SMS-Router | System calibration accessory | |
| *Calibration Microphone | <p>Standard Option</p>  <p><i>Piccolo II</i> Professional Class 2 Sound Level Meter Piccolo II Specs</p> | <p>Premium Option</p>  <p><i>MEZZO</i> Class 1 High Precision Microphone MEZZO Specs</p> |